



Resin Attachment (ø4 ~ ø16)

ZP3 Series

How to Order




ZP3 — ^{② Pad diameter} **10** ^{③ Material} **K P**

② Pad diameter (mm)	
Symbol	Applicable pad
04	ZP3-04B □
06	ZP3-06B □
08	ZP3-08B □
10	ZP3-10B □
13	ZP3-13B □
16	ZP3-16B □

③ Attachment material	
P	PEEK
GP	Conductive PEEK
M	POM
GM	Conductive POM

- No adsorption marks (rubber constituents) are left on the workpiece.
Avoids direct contact between the workpiece and the rubber by installing a PEEK attachment to the bellows pad to prevent the transfer of rubber constituents.
- Ideal for the **ZP3** series bellows pad (ø4 to ø16)

How to Order (When ordering with a pad)



- When ordering with a pad, put "***", below the part number of the pad as shown below. Note that the pad is not delivered with the attachment assembled.
- When the attachment is made of conductive PEEK, use conductive material for the pad.


<Precautions>

- Clean the product before using the attachment.
This product is not cleaned after machining. If the product is used in the condition in which it is shipped, residual material may be left on the work pieces. Clean before usage.
- If contact with hard material is a problem, do not use this product.

Dimensions

Green symbol is customized models. (mm)

K Resin Attachment



Model	②	Pad type	④	øA	øB	øC	D	P	Adapter pad no.	②	③	④
	Pad dia.		Pad Material							Pad dia.	Pad type	Pad Material
ZP3	04	K	P GP M GM	4	4.5	1.5	2.2	8.5	ZP3	06	B	N S U F GN GS
	06			6	7	1.6				08		
	08			8	9	3				10		
	10			10	11	5	3.2	10.5		13		
	13			13	14	7				16		
	16			16	17	8				20		

When the attachment is made of conductive PEEK, use conductive material for the pad.

Model for refer: **ZP3-08KGP** Adapter pad for refer: **ZP3-08BGN / ZP3-08BGS**